

High Security HP Enclosure



Alpha Introduces a High Security High Performance System

Alpha XM3-HP CableUPS:

Innovative transformer design and advanced intelligence maximize efficiency and reduce operating costs.



Alpha HP Enclosure:

Internal and external security enhancements provide increased protection against unauthorized entry.



AlphaCell HP:

Exclusive thin-plate, pure-lead design maximizes battery life and provides critical backup power.


Thermal Lid Design

Weld Tabs



Concealed Hinges

Flush Door Design



Battery bar attached with security screws and/or padlock



2-point hooked latch locks



Flush and reinforced door





Concealed hinges to limit accessibility

High Security HP Enclosure Specifications

Mechanical	
Dimensions H x W x D (in/mm):	29.14 x 28.30 x 17.12 / 740.16 x 718.82 x 434.85
Weight (lb/kg):	65 / 29.48
Details	
Material:	Exterior powdercoated aluminum
Vent Screen:	Mesh fabric with .005 x .005in / .12 x .12mm opening size to minimize snow, water and dust ingress
Door and Lid Seal:	Poron gasketing
Color:	Gray (custom colors available)
Lid:	Removable
Door:	Hinged, removable
Pole Mount:	Galvanized steel brackets for wood, and concrete pole mount and wall mount
Ground Mount:	Optional
Tamper Switch:	Optional
Battery Slide Tray:	Optional

Additional High Security Enclosure Features	
P/N: 746-323-20	Battery Security Bar
P/N: 746-324-20	Battery Security Padlock Tab
P/N: 746-387-21	LID Security Bolt Kit
P/N: 746-387-20	Door Security Bolt Kit
P/N: 746-322-20	Door Security Tabs (weld/padlock)

Integrated Northern Thermal Design

 Cool air intake through bottom of enclosure	 Thermally optimized sloped lid to maximize air flow
 No louvers in the door provides harsh weather protection	 Z-bracket design in lid exhaust protects from snow ingress and wind driven rain

Optional Internal Security Features

 Power supply security screw	 Battery security bar
---	---

External Locking Configurations

 2-point latch security with two locks	or	 3-point latch security with single lock
 8 - in - 1 Gem	or	 Single key access

Optional External Locking Security Features

 Up to 2 padlock/weld tabs	or	 Up to 4 corner security bolts
---	----	--

04/2013



Worldwide Corporate Offices

North America Tel: +1 360.647.2360 Fax: +1 360.671.4936	Europe Tel: +49 9122.79889.0 Fax: +49 9122.79889.21
--	--

Latin America Tel: +561 792.9651 Fax: +561 792.7157	Asia Pacific Tel: +852 2736.8663 Fax: +852 2199.7988
--	---





www.alpha.com