

## **Metered UPE-M Series**

**Outdoor Ground-Mount Enclosures** 



- Engineered for broadband powering applications
- CSA/UL certified to meet applicable industry standards
- Internal or external SUSE rated service entrance options available
- Aluminum welded construction and durable powdercoat finish exterior
- Portable generator cabling access door

## The UPE-M Series provide the cable operator a fully enclosed meter enclosure with high interrupt current protection.

In addition to the power supply equipment tray and sliding battery drawers, the UPE-M Series enclosure system includes integral line lugs, meter base, internal wiring and internal breaker.

## Alpha® Metered UPE-M Series Specifications

Mechanical			
Models:	UPE-M3	UPE-M6	UPE-M8
<b>Dimensions</b> H × W × D (in/mm):	45 × 26 × 19.7 / 1143 × 660 × 482	57.3 × 26 × 19.7 / 1455 × 660 × 482	50 × 32 × 20.5 / 1270 × 813 × 521
Weight (lb/kg):	100 / 44 (without batteries)	130 / 59 (without batteries)	140 / 64 (without batteries)
UPE-M Configurations:			
Specifications			
Material:	Exterior powdercoated aluminum		
Vent Screen:	Mesh fabric with .005 × .005in / .12 × .12mm opening size to minimize snow, water and dust ingress		
Door and Lid Seal:	Poron gasketing		
Color:	Grey (custom colors available)		
Lid:	Removable		
Door:	Removable/lockable		
Ground Mount:	Precast polymer concrete pad (optional)		
Tamper Switch:	Optional		



World Headquarters 2366 Bernville Road Reading, PA 19605 USA +1 610-208-1991 / +1 800-538-3627 **EnerSys EMEA** EH Europe GmbH Baarerstrasse 18 6300 Zug Switzerland EnerSys Asia 152 Beach Road Gateway East Building #11-08 Singapore 189721 / +65 6416-4800

For more information visit **www.enersys.com** © 2022 EnerSys. All Rights Reserved. Trademarks and logos are the property of EnerSys and its affiliates unless otherwise noted. Subject to revisions without prior notice. E.&O.E.

**2**07/2022