



an EnerSys® company

CPH 144

Central Power Hub



- Type 3R outdoor cabinet with heat exchanger for improved energy efficiency and reduced maintenance costs
- Provides up to 144 \pm 190Vdc line powering channels to power multiple devices and sites
- Wide AC input range (90 to 300Vac) for worldwide deployment
- High efficiency for reduced OPEX and carbon footprint
- Gas protector module and protector block panel provided for output surge protection for all channels

The Central Power Hub (CPH) is a Type 3R rated enclosure system designed to distribute up to 144 channels of \pm 190Vdc over OSP twisted copper pair cabling following the RFT-V standards. Applications include powering DSLAMs, security and surveillance remote nodes, ITS equipment, and wireless infrastructures.

The CPH-144 cabinet is installed in locations where 90 to 300Vac utility power is available, to power multiple remote communication equipment located thousands of feet away using energized twisted copper pair cabling. The CPH-144 enclosure system enables operators to reduce installation and operating expenses, and provides flexibility related to site selection for the remote equipment.

The system may include options such as 48Vdc strings of batteries, load center with main disconnect, generator inlet, TVSS, and heater.

The CPH-144 enclosure system incorporates a full range of standard features, including primary surge protection, current limiting, and individual ground fault interrupt for each circuit. Emphasis is placed on recognizing a fault condition and shutting down the circuit as quickly as possible to ensure the highest level of safety. Compliance with Telcordia GR-1089-CORE, Class A2 enables craftspeople to work on the equipment while powered which significantly reduces administrative overheads and labelling requirements, associated with high voltage wiring. Monitoring and control of the remote equipment is provided through the Cordex® CXC HP System Controller allowing the user to manage all aspects of their energy system.

CPH144 Central Power Hub Enclosure

Consult your Alpha representative for P/N configurations

Electrical	
Input voltage:	Nominal: 187 to 277Vac Operating: 187 to 310Vac Extended: 90 to 187Vac (de-rated power)
Input frequency:	45.0Hz to 66.0Hz
Power factor:	>98% (50 to 100% load)
THD:	<8% (50 to 100% load)
Efficiency:	90%
Output voltage:	±190Vdc
Output power:	10,800W max
Acoustic noise:	<65dba
Features	
Protection:	<ul style="list-style-type: none"> • Pad-lockable door handles • 40kA surge suppression • 50-pair protector panel for gas discharge tube modules
Mechanical	
Dimensions H x W x D:	1041 mm × 686 mm × 559 mm (41 in. × 27 in. × 22 in.)
Weight:	193 kg (425 lbs.)
Mounting:	<ul style="list-style-type: none"> • Ground • Pole
Cooling:	50W/°C heat exchanger

Environmental	
Temperature:	Operating: -40 to 46°C (-40 to 115°F); Storage: -40 to 85°C (-40 to 185°F)
Relative humidity:	5 to 95% non-condensing
Elevation:	-100 to 3,000 m (-330 to 9840 ft)
Cabinet Rating:	Type 3R
Agency compliance	
Cabinet Rating:	Type 3R
Safety:	<ul style="list-style-type: none"> • CSA/UL 60950-1-07 • CSA/UL 60950-21 • CSA/UL 60950-22



World Headquarters
2366 Bernville Road
Reading, PA 19605 USA
+1 610-208-1991 / +1 800-538-3627

EnerSys EMEA
EH Europe GmbH
Baarerstrasse 18
6300 Zug Switzerland

EnerSys Asia
152 Beach Road
Gateway East Building #11-08
Singapore 189721 / +65 6416 4800